



SLE Series Three Point Flail Mowers At Last You Have a Choice!



Available in working widths of 47 inches, 55 inches, 64 inches, and 74 inches, SLE Series Flail Mowers offer you the dependable performance you need to stay on the job! 40 years of experience go into the making of these machines.

Standard Features Include:

- Quick Hitch Compatible Category I Three Point
- Eurocardan Series 5 Driveline
- 3:1 Ratio Gearbox with Bevel Spiral Gears and Free Wheel
- Double Parking Stand
- No Tool Blade Change (Side Slicing Blades)
- Center or Offset Mounting
- Adjustable Working Height (Roller)
- Standard Multiposition Offsetable Hitch

Available Options:

- Side Skids
- Lateral Shields

Model	SLE-48	SLE-56	SLE-65	SLE-75
Working Width (Inches)	47	55	64	74
Rated Horsepower	20-45	25-45	30-45	35-45
Weight (LBS)	485	530	582	660
Number of Y Blades	44	52	60	72
Number of Ducksfoot	22	26	30	36
Hitch	3 point, I Cat.	3 point, I Cat.	3 point, I Cat.	3 point, I Cat.
Rotor Diameter (Inches)	4.5	4.5	4.5	4.5
Rotor Tube Thickness (Inches)	0.3125	0.3125	0.3125	0.3125
Swing Diameter (Inches)	14.6	14.6	14.6	14.6
Rear Roller Diameter (Inches)	5.5	5.5	5.5	5.5
Rotor Speed (RPM)	2356	2356	2356	2356
Knives Tip Speed (FPM)	8984	8984	8984	8984



For more information, contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893

Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997

Email: sales@unifarm.biz Web Site: www.unifarm.biz