



T10GE Series Gear Drive Rotary Tillers

Tiller Models from 58 to 80 Inches. The Heavy Duty Choice for Demanding Applications



Heavier than the T5 Series, the T10 Series Gear Drive Rotary Tillers from Phoenix are made to fit tractors from 30-50 horsepower. Heavy duty gear drive transmissions on these units guaranty years of trouble free operation under the most demanding applications.

Standard Features Include:

- Six Tines Per Flange
- Adjustable Upper and Lower Links
- Drive Housing Oil Level Site Glass
- Multi-position Heavy Duty Zinc Plated Jack Stand
- Powder Coat Paint Finish Available in Orange Or Red
- Heavy Duty Adjustable Drag Board W/Zinc Plated Check Chain
- Standard Series 5 PTO With Slip Clutch
- Heavy Duty Construction with Double Torque Tube and Single Piece Welded Center Hitch

Specifications	T10-58GE	T10-66GE	T10-74GE	T10-80GE
Working Width (Inches)	58	66	74	80
Working Depth (Inches)	4-8	4-8	4-8	4-8
Blades per Flange	6	6	6	6
Total Blades	42	48	54	60
Side Drive	Gear	Gear	Gear	Gear
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch	Slip Clutch
Hitch Category	Cat 1	Cat 1	Cat 1	Cat 1
PTO Shaft Series	5	5	5	5
PTO HP Required	35-50	35-50	35-50	35-50
Optimum PTO Speed (RPM)	540	540	540	540
Rotor Flange Diamater (Inches)	6.3	6.3	6.3	6.3
Rotor Flange Thickness (Inches)	0.5	0.5	0.5	0.5
Approximate Weight W/PTO (LBS)	646	679	712	765



For more information, contact:

Unifarm Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
 Email: sales@unifarm.biz Web Site: www.unifarm.biz