



## T15/4 Series Tillers from Phoenix Heavy Duty Gear Drive Tillers From 73 to 92 Inches



Phoenix T15 Series Rotary Tillers are built tough! Utilizing an ingenious load bearing box frame construction and oversize transmission components, these tillers offer flawless performance for as long as you need them on the job! Why settle for less when there is

**Phoenix!**

**Standard Features Include:**

- Four Speed Gearbox
- Six Tines per Flange, (Curved or Square)
- Adjustable Sliding Lower and Upper Links
- Heavy Duty Gear Drive in Oil Bath
- Welded Single Piece Top Hitch Frame
- High Gloss Powder Paint Finish

**Optional Equipment Includes:**

- Spiked Roller
- Wheel Kit
- Inward Turning End Tine
- Rotor With Knives Instead of Tine



Specifications	T15-72GE/4	T15-80GE/4	T15-90GE/4
Working Width (In.)	73	83	92
Working Depth (In.)	7	7	7
Blades / Flange	6	6	6
Total Blades	42	48	54
Side Drive	Gear	Gear	Gear
Driveline Protection	Slip Clutch	Slip Clutch	Slip Clutch
Hitch	Cat I and II	Cat I and II	Cat I and II
PTO Shaft Series	6	6	6
PTO Power Required (HP)	35-65	35-65	35-65
Optimum PTO Speed(RPM)	540	540	540
Rotor Flange Diameter (In.)	6.3	6.3	6.3
Rotor Flange Thickness (In.)	0.5	0.5	0.5
Approximate Weight W/PTO (LBS)	900	950	1050



For more information, contact:  
 Unifarm Machinery Corporation PO Box 38 (27894) 4608 Loly Road, Wilson, NC 27893  
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997  
 Email: sales@unifarm.biz Web Site: www.unifarm.biz