



T8 Series Rotary Tillers

Heavy Duty 62" and 74" Rotary Tillers

Quality and Performance at an Affordable Price



The Phoenix T8 family of rotary tillers are perfect for the independent week end gardner or horticultural enthusiast that likes to do things for themselves. No worries about these tillers, they are built for dependable trouble free performance year after year.

Standard Features Include:

- 6 Tines Per Flange for Smooth Tilling with Less Power
- Two Position and Adjustable/Off Setable Lower Hitch Blocks (for up to 4" of offset)
- Adjustable Skids
- Heavy Duty Castings and Bearings with Double Lip Seals.
- Powder Coat Paint Finish Available in Red Or Orange
- Heavy Duty Adjustable Drag Board With Zinc Plated Check Chain
- Standard Eurocardan Series 4 PTO Shaft With Slip Clutch
- Quick Hitch Compatible

| Specifications | T8-62 | T8-74 |
|--------------------------|-------------|-------------|
| Working Width (Inches) | 62 | 74 |
| Working Depth (Inches) | 7 | 7 |
| Blades per Flange | 6 | 6 |
| Scroll Diameter (Inches) | 15.7 | 15.7 |
| Total Blades | 24 | 30 |
| Rotor Flange Thickness | 3/8 | 3/8 |
| Rotor Speed (RPM) | 250 | 250 |
| Drive Chain | #80 | #80 |
| Driveline Protection | Slip Clutch | Slip Clutch |
| Hitch | Cat I | Cat I |
| PTO Shaft Series | 5 | 5 |
| PTO Power Required (HP) | 20-40 | 20-40 |
| Optimum PTO Speed (RPM) | 540 | 540 |
| Aproximate Weight (LBS) | 625 | 675 |



For more information, contact:
 Uniform Machinery Corporation PO Box 38 (27894) 4608 Lely Road, Wilson, NC 27893
 Phone: 252-291-3997 Fax: 252-291-7354 Toll Free: 877-294-3997
 Email: sales@unifarm.biz Web Site: www.unifarm.biz